



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 08.01.2016

revision 17.07.2015 (GB) Version 8.3

Epoxy Minute Adhesive Resin

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product

Epoxy Minute Adhesive Resin

Code-Nr. 105501

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Resin Component

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Postbox 48045, DE-8460 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail : msds@weicon.de

Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0

E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

GIZ Bonn (German, English) Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

Manufacturer

WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

Emergency advice

-

Phone -

GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)

Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315	
---------------	------	--

Eye Irrit. 2	H319	
--------------	------	--

Skin Sens. 1	H317	
--------------	------	--

Aquatic Chronic 2	H411	
-------------------	------	--

Hazard Statements

H315	Causes skin irritation.
------	-------------------------

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07



GHS09

Signal word

Warning

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P501	Dispose of contents/container to hazardous or special waste collection point.

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Resin for a two-component epoxy adhesive



Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Printed

08.01.2016

revision

17.07.2015 (GB) Version 8.3

Epoxy Minute Adhesive Resin

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	70 - 90	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
28064-14-4	608-164-0	Bisphenol F - epichlorhydrin resin with Number average Molecular Weight < 700	5 - 10	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411

REACH

CAS No	Name	REACH registration number
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26-xxxx

! SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately and dispose it safely.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

! In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

Rinse out mouth and give plenty of water to drink.

4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

vomiting

Respiratory complaints

Nausea

Confusion

skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

Keep under medical supervision for at least 48 hours.

Symptoms may not occur until several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet



Unsuitable extinguishing media
Full water jet

5.2. Special hazards arising from the substance or mixture
In case of fire formation of dangerous gases possible.
Nitrogen oxides (NO_x)
Carbon monoxide (CO)
Carbon dioxide (CO₂)

5.3. Advice for firefighters
Special protective equipment for fire-fighters
Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.
Do not inhale explosion and/or combustion gases.

Additional information
Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
For non-emergency personnel
Ensure adequate ventilation.
Use personal protective clothing.
Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions
Inform pollution control authorities if product gets into the sewerage systems or open waters.
Do not discharge into the drains/surface waters/groundwater.
Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up
Take up with absorbent material (e.g. sand, sawdust).
After taking up the material dispose according to regulation.

6.4. Reference to other sections
Safe handling: see section 7
Disposal: see section 13
Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Advice on safe handling
Avoid formation of aerosols.
Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures
Avoid contact with eyes and skin
Do not inhale gases/vapours/aerosols.

Hygiene measures
At work do not eat, drink and smoke.
Remove soiled or soaked clothing immediately.
Wash hands before breaks and after work.

Advice on protection against fire and explosion
Pay attention to general rules of internal fire prevention.



7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Advice on storage compatibility

Do not store with acids or alkalis.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Further information on storage conditions

Protect from direct solar radiation.

Store container at cool and aired place.

Store in a dry place.

Protect from heat/overheating.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No information available.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Breathing apparatus in the event of aerosol or mist formation.

! Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min;

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

liquid

Colour

yellow, clear

Odour

hardly noticeable

Odour threshold



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

08.01.2016

revision

17.07.2015 (GB) Version 8.3

Epoxy Minute Adhesive Resin

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	> 200 °C				
Melting point / Freezing point	not determined				
Flash point	> 150 °C				
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	1,17 g/cm3	20 °C			
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity kinematic	8000 - 15000 mPa*s	25 °C			
Viscosity dynamic	not determined				

Oxidising properties

No information available.

Explosive properties

No information available.

9.2. Other information

No information available.



SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

Reactions with strong acids.

Reactions with strong alkalis and oxidising agents.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

Substances to avoid

Alkali (lye), concentrated

Acid, concentrated

Oxidising agent, strong

10.6. Hazardous decomposition products

Nitrogen oxides (NO_x)

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
Skin irritation	irritant			
Eye irritation	irritant			
Skin sensitization	sensitizing			

Experiences made from practice

Sensitization through skin contact possible.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

**SECTION 12: Ecological information****12.1. Toxicity**

No information available.

12.2. Persistence and degradability

Elimination rate

Method of analysis

Method

Validation

**Biological
degradability**

not degradable

12.3. Bioaccumulative potential

Insoluble in water

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Recommendations for the product**

Cured material may be considered inert and disposed of as builders waste.

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

Untamminated packaging may be treated as household waste.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3082	3082	3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (BISPHENOL A EPOXY HARZ)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)	Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN)
14.3. Transport hazard class(es)	9	9	9
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes	Yes	Yes



14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 9

tunnel restriction code E

Classification code M6

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.2

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.