



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 25.11.2016

revision 22.11.2016 (GB) Version 1.0

### Easy-Mix HT 180 Hardener

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

#### Name of product

Easy-Mix HT 180 Hardener

Code-Nr. 106542

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Recommended intended purpose(s)

2-Component Epoxy Resin - Hardener Component

### 1.3. Details of the supplier of the safety data sheet

#### Distributor

WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail : msds@weicon.de

Internet : www.weicon.de

#### Advice

Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0

E-mail (competent person):

msds@weicon.de

### 1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

#### Manufacturer

WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

### 1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315	
---------------	------	--

Eye Irrit. 2	H319	
--------------	------	--

Skin Sens. 1	H317	
--------------	------	--

Aquatic Chronic 2	H411	
-------------------	------	--

#### Hazard Statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07



GHS09

### Signal word

Warning

### Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

### Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container to hazardous or special waste collection point.

### Hazardous ingredients for labeling

1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexan, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )

### Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. May produce an allergic reaction.

## 2.3. Other hazards

### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/ information on ingredients

### 3.1. Substances

not applicable

### 3.2. Mixtures

Hazardous ingredients



Safety Data Sheet according to Regulation (EC)  
No. 1907/2006 (REACH)

Printed

25.11.2016

revision

22.11.2016 (GB) Version 1.0

**Easy-Mix HT 180 Hardener**

**Hazardous ingredients (continued)**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	50 - 60	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
2530-83-8	219-784-2	[3-(2,3-Epoxypropoxy)propyl]trimethoxysilan	1 < 2,5	Skin Corr. 1, H318 / Aquatic Chronic 3, H412
60676-86-0	262-373-8	Siliciumdioxid, glasartig	15 - 25	
14228-73-0	238-098-4	1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexan	10 < 15	Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / Skin Sens. 1, H317 / Aquatic Chronic 3, H412

**REACH**

CAS No	Name	REACH registration number
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26-xxxx
2530-83-8	[3-(2,3-Epoxypropoxy)propyl]trimethoxysilan	01-2119513212-58

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

**In case of inhalation**

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

**In case of skin contact**

In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

**In case of eye contact**

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

**In case of ingestion**

Do not induce vomiting.

Refer to medical treatment.

**4.2. Most important symptoms and effects, both acute and delayed**

**Physician's information / possible symptoms**

vomiting

skin irritation

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Dry fire-extinguishing substance

ABC powder

Carbon dioxide

Water spray jet



---

**Unsuitable extinguishing media**

Halone  
Full water jet

**5.2. Special hazards arising from the substance or mixture**

In case of fire formation of dangerous gases possible.

Methanol  
Carbon monoxide (CO)  
Carbon dioxide (CO<sub>2</sub>)  
Formaldehyde vapours

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

**Additional information**

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.  
Collect contaminated firefighting water separately, must not be discharged into the drains.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Ensure adequate ventilation.  
Use personal protective clothing.  
Use breathing apparatus if exposed to vapours/dust/aerosol.

**6.2. Environmental precautions**

Inform pollution control authorities if product gets into the sewerage systems or open waters.  
Do not discharge into the drains or bodies of water..  
Do not discharge into the drains/surface waters/groundwater.

**6.3. Methods and material for containment and cleaning up**

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).  
Ventilate area concerned  
After taking up the material dispose according to regulation.

**6.4. Reference to other sections**

Safe handling: see section 7  
Disposal: see section 13  
Personal protection equipment: see section 8

---

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.  
Open and handle container with care!  
Take the usual precautions when handling with chemicals.

**General protective measures**

Do not inhale vapours.  
Avoid contact with eyes and skin  
Ensure sufficient ventilation.

**Hygiene measures**

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Pay attention to general rules of internal fire prevention.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep only in original container.

**Advice on storage compatibility**

Do not store with acids or alkalis.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

**Further information on storage conditions**

Keep container tightly closed and store at cool and aired place.

Keep barrel tightly closed.

Protect from heat and direct solar radiation.

Store in a dry place.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
60676-86-0	Silica, fused respirable dust	8 hours	0.08		EH40/2005

**DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	8,33 mg/kg bw/day	DNEL long-term dermal (local)	
		12,25 mg/m3	DNEL long-term inhalative (systemic)	
		8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
2530-83-8	[3-(2,3-Epoxypropoxy)propyl] trimethoxysilan	147 mg/m3	DNEL long-term inhalative (systemic)	
		21 mg/kg bw/day	DNEL long-term dermal (systemic)	

**PNEC**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	0,006 mg/l	PNEC aquatic, freshwater	



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 25.11.2016

revision 22.11.2016 (GB) Version 1.0

**Easy-Mix HT 180 Hardener****DNEL-/PNEC-values (continued)**

CAS No	Substance name	Value	Code	Remark
2530-83-8	[3-(2,3-Epoxypropoxy)propyl]trimethoxysilan	0,0006 mg/l	PNEC aquatic, marine water	
		10 mg/l	PNEC sewage treatment plant (STP)	
		0,996 mg/kg	PNEC sediment, freshwater	
		0,0996 mg/kg	PNEC sediment, marine water	
		1 mg/l	PNEC aquatic, freshwater	
		0,36 mg/kg dw	PNEC sediment, marine water	
		3,6 mg/kg dw	PNEC sediment, freshwater	
		0,1 mg/l	PNEC aquatic, marine water	
		10 mg/l	PNEC sewage treatment plant (STP)	

**Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls****Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short term: filter apparatus, filter A

**Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min; 60min.

**Eye protection**

tightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Sufficient ventilation and exhaustion.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

viscous

**Colour**

black

**Odour**

characteristic

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
pH value	not determined				



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 25.11.2016

revision 22.11.2016 (GB) Version 1.0

**Easy-Mix HT 180 Hardener**

	Value	Temperature	at	Method	Remark
<b>boiling point</b>	> 150 °C				
<b>melting point</b>	not determined				
<b>Flash point</b>	> 99 °C			closed cup	
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not applicable				
<b>Flammability (gas)</b>	not applicable				
<b>Ignition temperature</b>	not determined				
<b>Self ignition temperature</b>					The product is not self-igniting.
<b>Lower explosion limit</b>	not determined				
<b>Upper explosion limit</b>	not determined				
<b>Vapour pressure</b>	< 0,1 hPa	20 °C			
<b>Relative density</b>	1,089 g/cm3	20 °C			
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					insoluble
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity dynamic</b>	not determined				
<b>Viscosity kinematic</b>	> 10000 mm2/s	40 °C			
<b>Oxidising properties</b>	No information available.				
<b>Explosive properties</b>	no				
<b>9.2. Other information</b>	No information available.				

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

Reactions with acids, alkalies and oxidising agents.

Reactions with amines.

**10.4. Conditions to avoid**

Air, humid

Keep away from heat.

**10.5. Incompatible materials****Substances to avoid**

Alkali (lye)

Amines

Fluorine

Air, humid

Peroxide

Acid

Oxidising agent

Moisture.

**10.6. Hazardous decomposition products**

Gases/vapours, toxic

Carbon monoxide and carbon dioxide.

Formaldehyde

Hydrocarbons

Hydrogen

**Thermal decomposition**

Remark No decomposition if used as directed.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	> 2000 mg/kg	rat	OECD	CAS: 25068-38-6
<b>LD50 acute dermal</b>	> 2000 mg/kg	rabbit	OECD 402	CAS: 25068-38-6
<b>LC50 acute inhalation</b>	> 5,3 mg/l (4 h)	rat	OECD 403	CAS: 2530-83-8
<b>Skin irritation</b>	irritant			
<b>Eye irritation</b>	irritant			
<b>Skin sensitization</b>	sensitizing			

**Subacute Toxicity - Carcinogenicity**





## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 25.11.2016

revision 22.11.2016 (GB) Version 1.0

**Easy-Mix HT 180 Hardener**

Value	Species	Method	Validation
<b>Mutagenicity</b>			No experimental information on genotoxicity in vitro available.
<b>Reproduction-Toxicity</b>			No indications of toxic effects were observed in reproduction studies in animals.
<b>Carcinogenicity</b>			No indications of carcinogenic effects are available from long-term trials.

**Experiences made from practice**

Sensitization through skin contact possible.

Irritates eyes and skin.

**Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

**SECTION 12: Ecological information****12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
<b>Fish</b>	LC50 2,7 mg/l (96 h)	Oncorhynchus mykiss		CAS: 25068-38-6
<b>Daphnia</b>	NOEC 0,3 mg/l (21 d)	Daphnia magna	OECD 211	CAS: 25068-38-6
<b>Algae</b>	EC50 4,2 mg/l (72 h)	Pseudokirchneriella subcapitata		CAS: 25068-38-6

**12.2. Persistence and degradability**

	Elimination rate	Method of analysis	Method	Validation
<b>Biological degradability</b>	5 % (28 d) CAS: 25068-38-6		OECD 301 F	not readily degradable

**12.3. Bioaccumulative potential**

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects****General regulation**

Toxic to aquatic life with long lasting effects.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.



---

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Recommendations for the product**

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

**General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

---

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
<b>14.1. UN number</b>	3082	3082	3082
<b>14.2. UN proper shipping name</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (Epoxy Resin (BISPHENOL-A-EPICHLOROHYDRINPOLYMER))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (BISPHENOL-A-EPICHLOROHYDRINPOLYMER))	Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin (BISPHENOL-A-EPICHLOROHYDRINPOLYMER))
<b>14.3. Transport hazard class(es)</b>	9	9	9
<b>14.4. Packing group</b>	III	III	III
<b>14.5. Environmental hazards</b>	Yes	Yes	Yes
<b>14.6. Special precautions for user</b>	No information available.		
<b>14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	not applicable		
<b>Land and inland navigation transport ADR/RID</b>	Hazard label(s) 9 tunnel restriction code E Classification code M6		
<b>Marine transport IMDG</b>	MARINE POLLUTANT		

---

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 0 %

**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.



---

## SECTION 16: Other information

### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

### Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

- |      |  |
|------|--|
| H315 | Causes skin irritation.                            |
| H317 | May cause an allergic skin reaction.               |
| H318 | Causes serious eye damage.                         |
| H319 | Causes serious eye irritation.                     |
| H411 | Toxic to aquatic life with long lasting effects.   |
| H412 | Harmful to aquatic life with long lasting effects. |