

**Zinc-Alu-Spray****! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product Zinc-Alu-Spray
Code-Nr. 110020

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

Technical Aerosols

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Postbox 48045, DE-8460 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone ++49(0)251 / 9322 - 0
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

GIZ Bonn (German, English) Tel: ++49(0)228-19 240
TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178
433 7434 (24h Emergency Contact)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number**Emergency advice**

-
Phone -
GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)
Tel: ++49(0)228-19 240
TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178
433 7434 (24h Emergency Contact)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

| Hazard classes and Hazard categories | Hazard Statements | Classification procedure |
|--------------------------------------|-------------------|--------------------------|
|--------------------------------------|-------------------|--------------------------|

| | |
|-------------------|------------|
| Aerosol 1 | H222, H229 |
| Eye Irrit. 2 | H319 |
| STOT SE 3 | H336 |
| Aquatic Chronic 2 | H411 |

Hazard Statements

H222 Extremely flammable aerosol.

| | |
|------|--|
| H229 | Pressurised container: May burst if heated. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07



GHS09

Signal word

Danger

Hazard Statements

| | |
|------|--|
| H222 | Extremely flammable aerosol. |
| H229 | Pressurised container: May burst if heated. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary Statements

| | |
|--------------------|--|
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P264 | Wash hands thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P304 + P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell. |
| P337 + P313 | If eye irritation persists: Get medical advice/attention. |
| P403 | Store in a well-ventilated place. |
| P405 | Store locked up. |
| P410 + P412 | Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| P501 | Dispose of contents/container to hazardous or special waste collection point. |

! Hazardous ingredients for labeling

acetone, Solvent naphtha (petroleum), light arom. (NOTA P)

Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Caution! Container under pressure.

**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Zinc spray based on synthetic resin binder, solvent and pigments.

! Hazardous ingredients

| CAS No | EC No | Name | [% weight] | Classification according to Regulation (EC) No 1272/2008 [CLP/GHS] |
|------------|-----------|---|------------|--|
| 67-64-1 | 200-662-2 | acetone | 15 < 20 | Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336 |
| 106-97-8 | 203-448-7 | butane | 20 < 25 | Flam. Gas 1, H220 / Press. Gas |
| 7429-90-5 | 231-072-3 | aluminium powder (stabilised) | < 10 | Water-react. 2, H261 / Flam. Sol. 1, H228 |
| 141-78-6 | 205-500-4 | ethyl-acetate | 15 < 20 | Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336 |
| 7440-66-6 | 231-175-3 | zinc powder - zinc dust (stabilized) | 0,25 < 2,5 | Aquatic Acute 1, H400 / Aquatic Chronic 1, H410 |
| 64742-82-1 | 265-185-4 | Naphtha (petroleum), hydrotreated heavy (NOTA P) | 1 < 2,5 | Asp. Tox 1, H304 / STOT SE 3, H336 / Flam. Liq. 3, H226 / Aquatic Chronic 2, H411 / , EUH066 |
| 64742-95-6 | 265-199-0 | Solvent naphtha (petroleum), light arom. (NOTA P) | 2,5 < 10 | Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H335 / Aquatic Chronic 2, H411 / STOT SE 3, H336 / , EUH066 |
| 74-98-6 | 200-827-9 | propane | 20 < 25 | Flam. Gas 1, H220 / Press. Gas |
| 64742-48-9 | 265-150-3 | Naphtha (petroleum), hydrotreated heavy | 1 < 10 | Asp. Tox. 1, H304 |
| 1330-20-7 | 215-535-7 | xylene | 5 < 10 | Flam. Liq. 3, H226 / STOT RE 2, H373 / Asp. Tox. 1, H304 / Acute Tox. 4, H312, H332 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / STOT SE 3, H335 |

REACH

| CAS No | Name | REACH registration number |
|------------|---|---------------------------|
| 64742-82-1 | Naphtha (petroleum), hydrotreated heavy (NOTA P) | 01-2119458049-33 |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. (NOTA P) | 01-2119455851-35 |
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | 01-2119463258-33 |
| 1330-20-7 | xylene | 01-2119488216-32-xxxx |

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.



In case of ingestion

Do not induce vomiting.
Refer to medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

! SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam
Dry powder
Carbon dioxide
Dry sand

! Unsuitable extinguishing media

water

5.2. Special hazards arising from the substance or mixture

May lead to formation of explosive/easily ignitable vapour air mixtures.
Danger of bursting
In case of fire formation of dangerous gases possible.

5.3. Advice for firefighters

! Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.
Do not inhale explosion and/or combustion gases.

Additional information

Vapours are heavier than air and will spread on the ground.
Cool endangered containers with water spray jet.

! SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.
Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.
Do not discharge into the drains or bodies of water..
Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).
After taking up the material dispose according to regulation.

! Additional Information

Sort out leaky cans and dispose according to regulations.

**6.4. Reference to other sections**

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

! SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Take measures against electrostatically charging.

! General protective measures

Avoid contact with eyes and skin

Do not inhale aerosols

Ensure sufficient ventilation.

! Hygiene measures

At work do not eat, drink, smoke or take drugs.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

! Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

! Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

! Further information on storage conditions

Store at +5 till +25 °C.

Protect from direct solar radiation.

Keep container dry, tightly closed and store at cool place.

Keep container in a well-ventilated place

Storage temperature may not exceed 50°C (=122°F).

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

! SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

| CAS No | Name | Code | [mg/m3] | [ppm] | Remark |
|--------|------|------|---------|-------|--------|
|--------|------|------|---------|-------|--------|



Safety Data Sheet according to Regulation (EC)
No. 1907/2006 (REACH)

Printed 11.02.2016
revision 11.02.2016 (GB) Version 8.4

Zinc-Alu-Spray

Ingredients with occupational exposure limits to be monitored (continued)

| CAS No | Name | Code | [mg/m ³] | [ppm] | Remark |
|-----------|-------------------------------------|------------|----------------------|-------|-----------|
| 67-64-1 | Acetone | 8 hours | 1210 | 500 | EH40/2005 |
| | | Short-term | 3620 | 1500 | |
| 7429-90-5 | Aluminium metal: inhalable dust | 8 hours | 10 | | EH40/2005 |
| 7429-90-5 | Aluminium metal: respirable dust | 8 hours | 4 | | EH40/2005 |
| 106-97-8 | Butane | 8 hours | 1450 | 600 | EH40/2005 |
| | | Short-term | 1810 | 750 | |
| 141-78-6 | Ethyl acetate | 8 hours | | 200 | EH40/2005 |
| | | Short-term | | 400 | |
| 1330-20-7 | Xylene, o-, m-, p- or mixed isomers | 8 hours | 220 | 50 | EH40/2005 |
| | | Short-term | 441 | 100 | |

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

| CAS No | Name | Code | [mg/m ³] | [ppm] | Remark |
|---------|---------|---------|----------------------|-------|--------|
| 67-64-1 | acetone | 8 hours | 1210 | 500 | |

**DNEL-/PNEC-values
DNEL worker**

| CAS No | Substance name | Value | Code | Remark |
|------------|---|------------------------|--------------------------------------|-----------------------|
| 1330-20-7 | xylene | 289 mg/m ³ | DNEL acute inhalative (local) | |
| | | 289 mg/m ³ | DNEL acute inhalative (systemic) | |
| | | 77 mg/m ³ | DNEL long-term inhalative (systemic) | |
| | | 180 mg/kg | DNEL long-term dermal (systemic) | |
| | | 141-78-6 | ethyl-acetate | 734 mg/m ³ |
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | 1468 mg/m ³ | DNEL acute inhalative (local) | |
| | | 1468 mg/m ³ | DNEL acute inhalative (systemic) | |
| | | 63 mg/kg | DNEL long-term dermal (systemic) | |
| | | 300 mg/kg | DNEL long-term dermal (systemic) | |
| 7440-66-6 | zinc powder - zinc dust (stabilized) | 300 mg/kg | DNEL long-term dermal (systemic) | |
| | | 900 mg/m ³ | DNEL long-term inhalative (systemic) | |
| | | 5 mg/m ³ | DNEL long-term inhalative (systemic) | |
| | | 83 mg/kg | DNEL long-term dermal (systemic) | |

DNEL Consumer

| CAS No | Substance name | Value | Code | Remark |
|------------|---|----------|--------------------------------|--------|
| 64742-95-6 | Solvent naphtha (petroleum), light arom. (NOTA P) | 11 mg/kg | DNEL long-term oral (repeated) | |

PNEC

| CAS No | Substance name | Value | Code | Remark |
|-----------|----------------|-------------|-----------------------------|--------|
| 1330-20-7 | xylene | 12,46 mg/kg | PNEC sediment, freshwater | |
| | | 12,46 mg/kg | PNEC sediment, marine water | |
| | | 0,327 mg/l | PNEC aquatic, freshwater | |



Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Printed 11.02.2016
revision 11.02.2016 (GB) Version 8.4

Zinc-Alu-Spray

DNEL-/PNEC-values (continued)

| CAS No | Substance name | Value | Code | Remark |
|-----------|--------------------------------------|-------------|-----------------------------|--------|
| 141-78-6 | ethyl-acetate | 2,31 mg/kg | PNEC sediment, freshwater | |
| | | 0,327 mg/l | PNEC aquatic, marine water | |
| | | 0,024 mg/l | PNEC aquatic, marine water | |
| | | 0,24 mg/l | PNEC aquatic, freshwater | |
| | | 1,15 mg/kg | PNEC sediment, freshwater | |
| 67-64-1 | acetone | 0,115 mg/kg | PNEC sediment, marine water | |
| | | 10,6 mg/l | PNEC aquatic, freshwater | |
| | | 3,04 mg/kg | PNEC sediment, marine water | |
| | | 1,06 mg/l | PNEC aquatic, marine water | |
| 7440-66-6 | zinc powder - zinc dust (stabilized) | 30,4 mg/kg | PNEC sediment, freshwater | |
| | | 0,0206 mg/l | PNEC aquatic, freshwater | |
| | | 117,8 mg/kg | PNEC sediment, freshwater | |
| | | 0,0061 mg/l | PNEC aquatic, marine water | |
| | | 56,5 mg/kg | PNEC sediment, marine water | |

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

! Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Breathing apparatus in the event of aerosol or mist formation.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

aerosol

Colour

silver-grey

Odour

solvent-like

Odour threshold

**Zinc-Alu-Spray**

not determined

Important health, safety and environmental information

| | Value | Temperature | at | Method | Remark |
|--|----------------|-------------|----|--------|-----------------------------------|
| pH value | not determined | | | | |
| boiling point | -44 °C | | | | |
| melting point | not determined | | | | |
| Flash point | not applicable | | | | Aerosol |
| Vapourisation rate | not determined | | | | |
| Flammable (solid) | not determined | | | | |
| Flammability (gas) | not determined | | | | |
| Ignition temperature | > 200 °C | | | | estimate |
| Self ignition temperature | | | | | The product is not self-igniting. |
| Lower explosion limit | not determined | | | | |
| Upper explosion limit | not determined | | | | |
| Vapour pressure | not determined | | | | |
| Relative density | not determined | | | | |
| Vapour density | not determined | | | | |
| Solubility in water | | | | | immiscible |
| Solubility/other | not determined | | | | |
| Partition coefficient n-octanol/water (log P O/W) | not determined | | | | |
| Decomposition temperature | not determined | | | | |
| Viscosity dynamic | not applicable | | | | |
| Viscosity kinematic | not applicable | | | | |

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information

No information available.

**! SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

Formation of inflammable vapour-air mixtures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

| | Value/Validation | Species | Method | Remark |
|------------------------------|--|---------|-----------|-----------------|
| LD50 acute oral | > 2000 mg/kg | rat | | CAS: 64742-95-6 |
| LD50 acute dermal | > 2000 mg/kg | | | ATE |
| LC50 acute inhalation | > 5 mg/l (4 h) | | dust/mist | ATE |
| Skin irritation | low irritant effect - not necessary to label | | | |
| Eye irritation | irritant | | | |
| Skin sensitization | non-sensitizing | | | |

Subacute Toxicity - Carcinogenicity

| | Value | Species | Method | Validation |
|------------------------------|-------|---------|--------|---|
| Mutagenicity | | | | No experimental information on genotoxicity in vivo available. |
| Reproduction-Toxicity | | | | No indications of toxic effects were observed in reproduction studies in animals. |

**Zinc-Alu-Spray**

| Value | Species | Method | Validation |
|------------------------|---------|--------|---|
| Carcinogenicity | | | No indications of carcinogenic effects are available from long-term trials. |

! Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

! Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

Vapours may cause dizziness, headaches and tiredness

Product may cause irreversible eye injuries.

Inhalation causes narcotic effect/intoxication.

! Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

! SECTION 12: Ecological information**12.1. Toxicity**

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**! General regulation**

Toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

! SECTION 13: Disposal considerations**13.1. Waste treatment methods****Waste code No.**

16 05 04*

Name of waste

gases in pressure containers (including halons) containing hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

! Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.

**! General information**

For proper waste disposal a complete emptying of the tin is necessary.

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

! SECTION 14: Transport information

| | ADR/RID | IMDG | IATA-DGR |
|---|----------|------------------------|---------------------|
| 14.1. UN number | 1950 | 1950 | 1950 |
| 14.2. UN proper shipping name | AEROSOLS | AEROSOLS (ZINC POWDER) | Aerosols, flammable |
| 14.3. Transport hazard class(es) | 2.1 | 2.1 | 2.1 |
| 14.4. Packing group | - | - | - |
| 14.5. Environmental hazards | Yes | Yes | Yes |

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not applicable**Land and inland navigation transport ADR/RID**

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

MARINE POLLUTANT

Transport as limited quantities according to 3.4 IMDG Code is possible.

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 87,1 %

VOC value 622,8 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Zinc-Alu-Spray

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.3

| | |
|-----------------|--|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| H220 | Extremely flammable gas. |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H228 | Flammable solid. |
| H261 | In contact with water releases flammable gases. |
| H304 | May be fatal if swallowed and enters airways. |
| H312, | -?- |
| H332 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |