



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Name of product** Aluminium-Spray A-400  
Code-Nr. 110510

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Recommended intended purpose(s)

Technical Aerosols

### 1.3. Details of the supplier of the safety data sheet

#### Distributor

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Postbox 48045, DE-8460 Münster  
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

#### Advice

Produktsicherheit / Product-Safety-Department  
Phone ++49(0)251 / 9322 - 0  
E-mail (competent person):  
msds@weicon.de

### 1.4. Emergency telephone number

GIZ Bonn (German, English) Tel: ++49(0)228-19 240  
TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178  
433 7434 (24h Emergency Contact)

#### Manufacturer

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

### 1.4. Emergency telephone number

#### Emergency advice

-  
Phone -  
GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)  
Tel: ++49(0)228-19 240  
TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178  
433 7434 (24h Emergency Contact)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229
Eye Irrit. 2	H319
STOT SE 3	H336
Aquatic Chronic 3	H412

#### Hazard Statements

H222 Extremely flammable aerosol.

H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07

### Signal word

Danger

### Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

### Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container to hazardous or special waste collection point.

### Hazardous ingredients for labeling

acetone

### Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

Product has an anesthetic effect.

**Aluminium-Spray A-400****Information pertaining to special dangers for human and environment**

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

**3.2. Mixtures****Description**

Aluminium coloured laquer based on synthetic resin solvent and pigments.

**Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-64-1	200-662-2	acetone	15 < 20	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
74-98-6	200-827-9	propane	20 < 25	Flam. Gas 1, H220 / Press. Gas
106-97-8	203-448-7	butane	20 < 25	Flam. Gas 1, H220 / Press. Gas
123-86-4	204-658-1	n-butyl acetate	< 10	Flam. Liq. 3, H226 / STOT SE 3, H336
64742-95-6	265-199-0	Solvent naphtha (petroleum), light arom. (NOTA P)	10 < 15	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H335 / Aquatic Chronic 2, H411 / STOT SE 3, H336 / , EUH066
92045-53-9	295-434-2	Naphtha (petroleum), hydrodesulfurized light, dearomatized	2,5 < 5	Flam. Liq. 2, H225 / Skin Irrit. 2, H315 / Asp. Tox., H304 / Aquatic Chronic 2, H411 / STOT SE 3, H336
7429-90-5	231-072-3	Aluminium	< 10	Flam. Sol. 1, H228
64742-48-9	265-150-3	Naphtha (petroleum), hydrotreated heavy	1 < 10	Asp. Tox. 1, H304
64742-49-0	265-151-9	Naphtha (petroleum), hydrotreated light	1 < 2,5	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 2, H411

**REACH**

CAS No	Name	REACH registration number
7429-90-5	Aluminium	01-2119529243-45

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

**In case of inhalation**

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

**In case of skin contact**

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

**In case of eye contact**

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

**In case of ingestion**

Do not induce vomiting.

Call for a doctor immediately.



---

**4.2. Most important symptoms and effects, both acute and delayed**

**Physician's information / possible symptoms**

The following symptoms may occur:

Unconsciousness  
Anaesthetic state  
Headache  
Confusion  
Dizziness

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

---

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Alcohol-resistant foam  
Dry fire-extinguishing substance  
Carbon dioxide  
sand

**Unsuitable extinguishing media**

water  
Full water jet

**5.2. Special hazards arising from the substance or mixture**

Danger of bursting  
In case of fire formation of dangerous gases possible.

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

**Additional information**

Cool endangered containers with water spray jet.  
Collect contaminated firefighting water separately, must not be discharged into the drains.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Ensure adequate ventilation.  
Use personal protective clothing.  
Keep away sources of ignition.

**6.2. Environmental precautions**

Inform pollution control authorities if product gets into the sewerage systems or open waters.  
Do not discharge into the drains/surface waters/groundwater.

**6.3. Methods and material for containment and cleaning up**

Take up with absorbent material.  
After taking up the material dispose according to regulation.

**6.4. Reference to other sections**

Safe handling: see section 7  
Disposal: see section 13  
Personal protection equipment: see section 8

**Aluminium-Spray A-400****SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**General protective measures**

Avoid contact with eyes and skin

Do not inhale aerosols

**Hygiene measures**

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn even after use.

Protect from heat and sunlight.

Take precautionary measures against static discharges.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

**Further information on storage conditions**

Protect from direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Store in a dry place.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
67-64-1	Acetone	8 hours Short-term	1210 3620	500 1500	EH40/2005
7429-90-5	Aluminium metal: inhalable dust	8 hours	10		EH40/2005
7429-90-5	Aluminium metal: respirable dust	8 hours	4		EH40/2005
106-97-8	Butane	8 hours Short-term	1450 1810	600 750	EH40/2005
109-87-5	Dimethoxymethane	8 hours Short-term	3160 3950	160 1250	EH40/2005



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 08.01.2016

revision 27.11.2015 (GB) Version 8.4

## Aluminium-Spray A-400

### Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
67-64-1	acetone	8 hours	1210	500	

#### Additional advice

The statutory local and national regulations have to be observed.

### 8.2. Exposure controls

#### Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

#### Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

#### Eye protection

tightly fitting goggles

#### Other protection measures

protective clothing

#### Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

## ! SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

aerosol

#### Colour

grey

#### Odour

characteristic

#### Odour threshold

not determined

### Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not determined				
<b>boiling point</b>	not applicable				
<b>Melting point / Freezing point</b>	not determined				
<b>Flash point</b>	not applicable				Aerosol
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not determined				
<b>Flammability (gas)</b>	not determined				
<b>Ignition temperature</b>	> 200 °C				estimate



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 08.01.2016

revision 27.11.2015 (GB) Version 8.4

## Aluminium-Spray A-400

	Value	Temperature	at	Method	Remark
<b>Self ignition temperature</b>					The product is not self-igniting.
<b>Lower explosion limit</b>	not determined				
<b>Upper explosion limit</b>	not determined				
<b>Vapour pressure</b>	not determined	20 °C			
<b>Relative density</b>	not determined				
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>	not determined				
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity dynamic</b>	not determined				
<b>Viscosity kinematic</b>	not determined				

### Oxidising properties

No information available.

### Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

### 9.2. Other information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No information available.

### 10.3. Possibility of hazardous reactions

No information available.

### 10.4. Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products



### Thermal decomposition

Remark No decomposition if used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
<b>LC50 acute inhalation</b>	> 5 mg/l (4 h)	rat		Aluminium
<b>Skin irritation</b>	irritant			
<b>Eye irritation</b>	irritant			

#### Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.  
When inhaled, reaction time and coordination sense may be reduced.  
Product may cause irreversible eye injuries.  
Inhalation causes headache/nausea.  
Irritates eyes and skin.  
Inhalation causes narcotic effect/intoxication.

#### Additional information

The product is to be handled with the caution usual with chemicals.  
Other hazardous properties may not be excluded.

## SECTION 12: Ecological information

### 12.1. Toxicity

No information available.

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

No information available.

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

#### General regulation

Harmful to aquatic life with long lasting effects.  
Do not allow uncontrolled leakage of product into the environment.  
Product is not allowed to be discharged into aquatic environment.



## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste code No.**

16 05 04\*

**Name of waste**

gases in pressure containers (including halons) containing hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

**General information**

For proper waste disposal a complete emptying of the tin is necessary.

## SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

**14.6. Special precautions for user**

Caution: Gases

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**Land and inland navigation transport ADR/RID**

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

**Marine transport IMDG**

Transport as limited quantities according to 3.4 IMDG Code is possible.

**Transport/further information**

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

## ! SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC standard**

VOC content 83,6 %

VOC value 595 g/L

---

**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

---

**! SECTION 16: Other information****! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

**Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.3

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.