



Safety Data Sheet according to Regulation (EC)  
No. 1907/2006 (REACH)

Printed 11.01.2016  
revision 18.06.2015 (GB) Version 8.3

**Starter Spray**

**! SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Name of product**

Starter Spray  
Code-Nr. 116600

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Recommended intended purpose(s)**

Technical Aerosols

**1.3. Details of the supplier of the safety data sheet**

**Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Postbox 48045, DE-8460 Münster  
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone ++49(0)251 / 9322 - 0  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

GIZ Bonn (German, English) Tel: ++49(0)228-19 240  
TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178  
433 7434 (24h Emergency Contact)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number**

**Emergency advice**

-  
Phone -  
GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)  
Tel: ++49(0)228-19 240  
TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178  
433 7434 (24h Emergency Contact)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229	
Skin Irrit. 2	H315	
STOT SE 3	H336	
Aquatic Chronic 3	H412	

**Hazard Statements**

H222	Extremely flammable aerosol.
------	------------------------------

H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07

### Signal word

Danger

### Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

### Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container to hazardous or special waste collection point.

### ! Hazardous ingredients for labeling

diethylether, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

### Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

Product has an anesthetic effect.



# Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Printed  
revision

11.01.2016  
18.06.2015 (GB) Version 8.3

## Starter Spray

### ! Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

### ! Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## ! SECTION 3: Composition/ information on ingredients

### 3.1. Substances

not applicable

### 3.2. Mixtures

#### Description

Mixture of active ingredients with propellant

#### Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
60-29-7	200-467-2	diethylether	25 - 50	Flam. Liq. 1, H224 / Acute Tox. 4, H302 / STOT SE 3, H336
74-98-6	200-827-9	propane	10 - 20	Flam. Gas 1, H220 / Press. Gas
75-28-5	200-857-2	isobutane	25 - 50	Flam. Gas 1, H220 / Press. Gas
106-97-8	203-448-7	butane	2,5 - 10	Flam. Gas 1, H220 / Press. Gas
64742-49-0	927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	2,5 - 10	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336
64742-49-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	2,5 - 10	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336

#### REACH

CAS No	Name	REACH registration number
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	01-2119475515-33
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	01-2119475514-35-xxxx

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.

Symptoms of poisoning may not occur for many hours, therefore keep under medical supervision for at least 48 hours.

#### In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off with water.

Consult a doctor if skin irritation persists.

#### In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

#### In case of ingestion

Do not induce vomiting.

Refer to medical treatment.



**Starter Spray**

---

**4.2. Most important symptoms and effects, both acute and delayed**

**Physician's information / possible symptoms**

The following symptoms may occur:

Unconsciousness

Anaesthetic state

Headache

Confusion

**4.3. Indication of any immediate medical attention and special treatment needed**

**Treatment (Advice to doctor)**

Keep under medical supervision for at least 48 hours.

---

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Foam

Dry powder

Carbon dioxide

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

May lead to formation of explosive/easily ignitable vapour air mixtures.

Danger of bursting

In case of fire formation of dangerous gases possible.

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

**Additional information**

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

**6.2. Environmental precautions**

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

**6.3. Methods and material for containment and cleaning up**

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

**Additional Information**

Sort out leaky cans and dispose according to regulations.

**Starter Spray****6.4. Reference to other sections**

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

**! SECTION 7: Handling and storage****7.1. Precautions for safe handling****! Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**General protective measures**

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

**Hygiene measures**

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Avoid effect of heat.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

**Further information on storage conditions**

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Recommended storage temperature: room temperature.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
60-29-7	Diethyl ether	8 hours	310	100	EH40/2005
		Short-term	620	200	



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

11.01.2016

revision

18.06.2015 (GB) Version 8.3

## Starter Spray

### Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
60-29-7	diethylether	8 hours	308	100	
		Short-term	616	200	

#### ! Additional advice

The statutory local and national regulations have to be observed.

#### 8.2. Exposure controls

##### Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short term: filter apparatus, filter AX

#### ! Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

#### ! Eye protection

tightly fitting goggles

#### Other protection measures

protective clothing

#### Appropriate engineering controls

Sufficient ventilation and exhaustion.

## ! SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

aerosol

#### Colour

colourless

#### Odour

characteristic

#### Odour threshold

not determined

### Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				
Melting point / Freezing point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 200 °C				



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

11.01.2016

revision

18.06.2015 (GB) Version 8.3

## Starter Spray

	Value	Temperature	at	Method	Remark
<b>Self ignition temperature</b>					The product is not self-igniting.
<b>Lower explosion limit</b>	not determined				
<b>Upper explosion limit</b>	not determined				
<b>Vapour pressure</b>	not determined				
<b>Relative density</b>	0,61 g/cm <sup>3</sup>	20 °C			
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					No or low immiscibility
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity</b>	not determined				
<b>Solvent content</b>	100 %				
<b>Oxidising properties</b>	No information available.				
<b>Explosive properties</b>	The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .				
<b>9.2. Other information</b>	No information available.				

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No information available.

### 10.3. Possibility of hazardous reactions

No information available.

### 10.4. Conditions to avoid

Keep away from heat.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.



#### Thermal decomposition

Remark No decomposition if used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	1215 mg/kg	rat		Diethyl ether
<b>LD50 acute dermal</b>	> 2920 mg/kg	rat		hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes
<b>LC50 acute inhalation</b>	> 50 mg/l (4 h)	rat		Isobutane
<b>Skin irritation</b>	non-irritant			
<b>Eye irritation</b>	non-irritant			
<b>Skin sensitization</b>	non-sensitizing			

#### Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

When inhaled, reaction time and coordination sense may be reduced.

Risk of strong health injuries in case of long-term exposition.

Inhalation causes headache/nausea.

Inhalation causes narcotic effect/intoxication.

#### Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

## ! SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicological effects

	Value	Species	Method	Validation
<b>Daphnia</b>	EC50 3 mg/l (48 h)	Daphnia magna		hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

No information available.

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects



**Starter Spray****! General regulation**

Toxic to aquatic life, fishes and plankton.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

**! SECTION 13: Disposal considerations****13.1. Waste treatment methods****Waste code No.**

15 01 04

16 05 04\*

**Name of waste**

metallic packaging

gases in pressure containers (including halons) containing hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

**! General information**

For proper waste disposal a complete emptying of the tin is necessary.

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
<b>14.1. UN number</b>	1950	1950	1950
<b>14.2. UN proper shipping name</b>	AEROSOLS	AEROSOLS	Aerosols, flammable
<b>14.3. Transport hazard class(es)</b>	2.1	2.1	2.1
<b>14.4. Packing group</b>	-	-	-
<b>14.5. Environmental hazards</b>	No	No	No

**14.6. Special precautions for user**

Caution: Gases

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**Land and inland navigation transport ADR/RID**

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

**Transport/further information**

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)



---

## ! SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### ! VOC standard

VOC content	100 %
VOC value	613,5 g/L

### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

---

## ! SECTION 16: Other information

### ! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

#### Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.2

H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.