



---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Name of product**

Primer P 400

Code-Nr. 135504

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Uses advised against**

**Remark**

Do not use for private purposes (household).

**Recommended intended purpose(s)**

to be used as surface preconditioning

### 1.3. Details of the supplier of the safety data sheet

**Distributor**

WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Postbox 48045, DE-8460 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail : [msds@weicon.de](mailto:msds@weicon.de)

Internet : [www.weicon.de](http://www.weicon.de)

**Advice**

Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0

E-mail (competent person):

[msds@weicon.de](mailto:msds@weicon.de)

### 1.4. Emergency telephone number

GIZ Bonn (German, English) Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

**Manufacturer**

WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

### 1.4. Emergency telephone number

**Emergency advice**

-

Phone -

GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)

Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

---

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Flam. Liq. 2	H225	
Skin Irrit. 2	H315	
Repr. 2	H361d	
STOT SE 3	H336	
STOT RE 2	H373	
Asp. Tox. 1	H304	

### Hazard Statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07



GHS08

### Signal word

Danger

### Hazard Statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

### Precautionary Statements

P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

06.01.2016

revision

18.06.2015 (GB) Version 8.3

## Primer P 400

P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing.
P370 + P378	In case of fire: Use foam for extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

### Hazardous ingredients for labeling

toluene, xylene

### Additional information

#### Remark

For industrial use only.

#### 2.3. Other hazards

Product has an anesthetic effect.

### Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Possible risk of harm to the unborn child.

### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/ information on ingredients

### 3.1. Substances

not applicable

### 3.2. Mixtures

#### Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
100-41-4	202-849-4	ethylbenzene	< 2	Flam. Liq. 2, H225 / Acute Tox. 4, H332 / STOT RE 2, H373 (hearing organs) / Asp. Tox. 1, H304
108-88-3	203-625-9	toluene	50 - 99,99	Flam. Liq. 2, H225 / Repr. 2, H361d / Asp. Tox. 1, H304 / STOT RE 2, H373 / Skin Irrit. 2, H315 / STOT SE 3, H336
1330-20-7	215-535-7	xylene	< 10	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Acute Tox. 4, H312 / Skin Irrit. 2, H315

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.

#### In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.



---

**In case of skin contact**

Dab affected skin part with a cotton ball or cellulose and wash it afterwards with plenty of water and a mild cleaner.  
Consult a doctor if skin irritation persists.

**In case of eye contact**

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

**In case of ingestion**

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Call for a doctor immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

**Physician's information / possible symptoms**

Unconsciousness

Respiratory complaints

Confusion

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

---

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

In case of fire formation of dangerous gases possible.

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

**Additional information**

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

**6.2. Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.



### 6.3. Methods and material for containment and cleaning up

Disposal according to regulations.

Take up mechanically.

### 6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Take the usual precautions when handling with chemicals.

#### General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

It is essential for pregnant women to avoid inhaling the product and not to let it come in contact with the skin.

#### Hygiene measures

At work do not eat, drink and smoke.

Keep away from food and drink.

Keep separated from food and feed.

Wash hands before breaks and after work.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Prevent penetration into the ground.

#### Advice on storage compatibility

Do not store together with food.

#### Further information on storage conditions

Store closed container at cool and aired place.

Protect from frost.

Protect from heat and direct solar radiation.

Store in a dry place.

Protect from heat/overheating.

### 7.3. Specific end use(s)

#### Recommendation(s) for intended use

See section 1.2

## ! SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
100-41-4	Ethylbenzene	8 hours	441	100	EH40/2005
		Short-term	552	125	



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

06.01.2016

revision

18.06.2015 (GB) Version 8.3

## Primer P 400

## Ingredients with occupational exposure limits to be monitored (continued)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
108-88-3	Toluene	8 hours	191	50	EH40/2005
		Short-term	574	150	
1330-20-7	Xylene, o-, m-, p- or mixed isomers	8 hours	220	50	EH40/2005
		Short-term	441	100	

## Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
100-41-4	ethylbenzene	8 hours	442	100	skin
		Short-term	884	200	
108-88-3	toluene	8 hours	192	50	skin
		Short-term	384	100	
1330-20-7	xylene, mixed isomers, pure	8 hours	221	50	skin
		Short-term	442	100	

## Additional advice

The statutory local and national regulations have to be observed.

## 8.2. Exposure controls

## Respiratory protection

If ventilation insufficient, wear respiratory protection.

Breathing apparatus with combination filter A2/P2

## ! Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: fluorinated rubber; 0,7mm; 480min; 60min;

## Eye protection

tightly fitting goggles

## Other protection measures

protective clothing

## Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

## Appearance

liquid

## Colour

yellowish

## Odour

solvent-like

## Odour threshold

not determined

## Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	111 °C				



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

06.01.2016

revision

18.06.2015 (GB) Version 8.3

**Primer P 400**

	Value	Temperature	at	Method	Remark
<b>Melting point / Freezing point</b>	not determined				
<b>Flash point</b>	4 °C				
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not determined				
<b>Flammability (gas)</b>	not determined				
<b>Ignition temperature</b>	430 °C				
<b>Self ignition temperature</b>	not determined				
<b>Lower explosion limit</b>	1,0 Vol-%				
<b>Upper explosion limit</b>	7,8 Vol-%				
<b>Vapour pressure</b>	29 hPa	20 °C			
<b>Relative density</b>	0,87 g/cm <sup>3</sup>	20 °C			
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					insoluble
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity kinematic</b>	11 s	20 °C		4 DIN 53211	
<b>Solvent content</b>	97 %				
<b>Oxidising properties</b>	No information available.				
<b>Explosive properties</b>	Explo. Gr.: IIA (gem. 94/9/EG ATEX)				
<b>9.2. Other information</b>	No information available.				

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

### 10.3. Possibility of hazardous reactions

Reactions with strong oxidising agents.  
Reactions with strong alkalies.

### 10.4. Conditions to avoid

Keep away from heat.

### 10.5. Incompatible materials

#### Substances to avoid

Alkali (lye), concentrated  
Oxidising agent, strong

### 10.6. Hazardous decomposition products

Hydrogen chloride (HCl)

### Thermal decomposition

Remark No decomposition if used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	3523 mg/kg	rat		CAS: 1330-20-7
<b>LD50 acute dermal</b>	12124 mg/kg	rabbit		CAS: 108-88-3
<b>LC50 acute inhalation</b>	5320 mg/l (4 h)	mouse		CAS: 108-88-3
<b>Skin irritation</b>	irritant			

#### Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
<b>Mutagenicity</b>				Information on genotoxicity in vitro available.

#### Specific target organ toxicity (repeated exposure)

May cause damage to organs, if longer exposed.

#### Experiences made from practice

Vapours may cause dizziness, headaches and tiredness  
Harmful to health by prolonged exposure.  
Risk of strong health injuries in case of long-term exposition.  
Frequent persistent contact with the skin may cause skin irritation.

#### Additional information

The product is to be handled with the caution usual with chemicals.  
Other hazardous properties may not be excluded.





## SECTION 12: Ecological information

### 12.1. Toxicity

No information available.

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

No information available.

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

#### General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Recommendations for the product

Remove in accordance with local official regulations.

There are no harmonised regulations on the disposal of chemicals in the member states of the EU. In Germany the Recycling and Waste Management Act (KrWG) stipulates recycling as a requirement.

This means that a distinction must be made between "wastes for recycling" and "wastes for disposal". Particular aspects - in the main concerning delivery - are also governed by the Laender.

#### Recommendations for packaging

Dispose of according to the local waste regulations.

## SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1294	1294	1294
14.2. UN proper shipping name	TOLUENE (toluene)	TOLUENE (toluene)	Toluene (toluene)
14.3. Transport hazard class(es)	3	3	3
14.4. Packing group	II	II	II
14.5. Environmental hazards	No	No	No
14.6. Special precautions for user	Caution: FLAMMABLE LIQUID		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	not applicable		



---

**Land and inland navigation transport ADR/RID**

Hazard label(s) 3

tunnel restriction code D/E

Classification code F1

**Transport/further information**

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

---

**! SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**! VOC standard**

VOC content 97 %

VOC value 844 g/L

**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

---

**SECTION 16: Other information**

**Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

**Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.2

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

H373 May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).