

**Aluminium Paint****SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Name of product** Aluminium Paint  
Code-Nr. 150020

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended intended purpose(s)**

Technical Liquids

**1.3. Details of the supplier of the safety data sheet****Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Postbox 48045, DE-8460 Münster  
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone ++49(0)251 / 9322 - 0  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

GIZ Bonn (German, English) Tel: ++49(0)228-19 240  
TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178  
433 7434 (24h Emergency Contact)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number****Emergency advice**

-  
Phone -  
GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)  
Tel: ++49(0)228-19 240  
TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178  
433 7434 (24h Emergency Contact)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Flam. Liq. 3	H226	
STOT SE 3	H336	
Aquatic Chronic 2	H411	

**Hazard Statements**

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07



GHS09

### ! Signal word

Warning

### Hazard Statements

H226 Flammable liquid and vapour.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

### Precautionary Statements

P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 Keep container tightly closed.  
 P243 Take precautionary measures against static discharge.  
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P362 Take off contaminated clothing.  
 P370 + P378 In case of fire: Use dry sand to extinguish.  
 P391 Collect spillage.  
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403 + P235 Store in a well-ventilated place. Keep cool.  
 P501 Dispose of contents/container to hazardous or special waste collection point.

### ! Hazardous ingredients for labeling

Solvent naphtha (petroleum), light arom. (NOTA P), Naphtha (petroleum), hydrodesulfurized heavy, xylene

### Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

### Special rules for supplemental label elements for certain mixtures

Contains 2-Butanonoxim, Butanonoxim . May produce an allergic reaction.

## 2.3. Other hazards

### Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



## Aluminium Paint

### ! SECTION 3: Composition/ information on ingredients

#### 3.1. Substances

not applicable

#### 3.2. Mixtures

##### Description

Coating paint

#### ! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
96-29-7	202-496-6	2-butanone oxime	0,1 < 1	Carc. 2, H351 / Acute Tox. 4, H312 / Eye Dam. 1, H318 / Skin Sens. 1, H317
1330-20-7	215-535-7	xylene	5 < 10	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Acute Tox. 4, H312 / Skin Irrit. 2, H315
64742-95-6	265-199-0	Solvent naphtha (petroleum), light arom. (NOTA P)	2,5 < 10	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H335 / Aquatic Chronic 2, H411 / STOT SE 3, H336 / , EUH066
7429-90-5	231-072-3	Aluminium	10 < 20	Flam. Sol. 1, H228
64742-82-1	265-185-4	Naphtha (petroleum), hydrodesulfurized heavy	25 < 50	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / STOT SE 3, H336

#### REACH

CAS No	Name	REACH registration number
7429-90-5	Aluminium	01-2119529243-45
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	01-2119458049-33

#### Additional advice

<49,2% volatile organic compound (FOV)

### ! SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Remove contaminated soaked clothing immediately.

##### In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

##### In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

##### In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

#### ! In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

##### Physician's information / possible symptoms

Coughing

vomiting

Headache

Nausea

Confusion

skin irritation



---

**4.3. Indication of any immediate medical attention and special treatment needed**

**Treatment (Advice to doctor)**

If swallowed or in the event of vomiting, risk of entering the lungs.

---

**! SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**! Suitable extinguishing media**

Foam  
Dry powder  
Dry sand

**! Unsuitable extinguishing media**

water

**5.2. Special hazards arising from the substance or mixture**

In case of fire formation of dangerous gases possible.

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

**Additional information**

Cool endangered containers with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.  
Collect contaminated firefighting water separately, must not be discharged into the drains.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Remove persons to safety.  
Use personal protective clothing.  
Keep away sources of ignition.

**6.2. Environmental precautions**

Inform pollution control authorities if product gets into the sewerage systems or open waters.  
Do not discharge into the drains or bodies of water..  
Do not discharge into the drains/surface waters/groundwater.

**6.3. Methods and material for containment and cleaning up**

Protect from water.  
Disposal according to regulations.  
Take up with absorbent material (e.g. sand, sawdust).

**Additional Information**

Sort out leaky cans and dispose according to regulations.

**6.4. Reference to other sections**

Safe handling: see section 7  
Disposal: see section 13  
Personal protection equipment: see section 8

**! SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed.

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**General protective measures**

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

**Hygiene measures**

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking

Protect from heat and sunlight.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

**! Advice on storage compatibility**

Do not store with acids.

Keep at distance to ignition device, water and alkalies.

Do not store together with oxidizing agents.

**! Further information on storage conditions**

Protect from frost.

Store container at cool and aired place.

Store in a dry place.

Protect from heat/overheating.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
7429-90-5	Aluminium metal: inhalable dust	8 hours	10		EH40/2005
7429-90-5	Aluminium metal: respirable dust	8 hours	4		EH40/2005
1330-20-7	Xylene, o-, m-, p- or mixed isomers	8 hours Short-term	220 441	50 100	EH40/2005

**Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)**

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
1330-20-7	xylene, mixed isomers, pure	8 hours Short-term	221 442	50 100	skin

**Aluminium Paint****Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls****! Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Breathing apparatus in the event of aerosol or mist formation.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

**! Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

**Eye protection**

tightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Sufficient ventilation and exhaustion.

**! SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

liquid

**Colour**

silver-coloured

**Odour**

solvent-like

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not determined				
<b>boiling point</b>	137 °C				
<b>melting point</b>	not determined				
<b>Flash point</b>	30 °C				
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not determined				
<b>Flammability (gas)</b>	not determined				
<b>Ignition temperature</b>	not determined				
<b>Self ignition temperature</b>	not determined				
<b>Lower explosion limit</b>	not determined				
<b>Upper explosion limit</b>	not determined				



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 06.01.2016

revision 30.11.2015 (GB) Version 8.5

**Aluminium Paint**

	Value	Temperature	at	Method	Remark
<b>Vapour pressure</b>	not applicable				
<b>Relative density</b>	1 g/cm <sup>3</sup>				
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					insoluble
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity consistency 4 mm</b>	ca. 120 s			6 DIN/ISO 2431	
<b>Viscosity kinematic</b>	> 21 mm <sup>2</sup> /s	40 °C			

**Oxidising properties**

No information available.

**Explosive properties**

No information available.

**9.2. Other information**

No information available.

**! SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

Reactions with strong acids.

Reactions with strong oxidising agents.

Formation of explosive gas/air mixtures.

Reactions with water.

Reactions with alkalies.

**10.4. Conditions to avoid**

After contact with water:

hydrogen

Keep away from heat.

**10.5. Incompatible materials****Substances to avoid**

Alkali (lye)

Acid, concentrated

Oxidising agent, strong

Water

Keep away from heat.

**10.6. Hazardous decomposition products**

Gases/vapours, toxic

**Thermal decomposition**

Remark No decomposition if used as directed.

**! SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	> 5000 mg/kg	rat		CAS: 64742-82-1
<b>LD50 acute dermal</b>	> 2000 mg/kg			ATE
<b>LC50 acute inhalation</b>	> 20 mg/l (4 h)			ATE
<b>Skin irritation</b>	low irritant effect - not necessary to label			
<b>Eye irritation</b>	low irritant			
<b>Skin sensitization</b>	sensitizing			

**! Specific target organ toxicity (single exposure)**

May cause drowsiness or dizziness.

**! Experiences made from practice**

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

May cause vomiting.

May irritate the mucosae.

When inhaled, reaction time and coordination sense may be reduced.

Sensitization through skin contact possible.

**Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

**! SECTION 12: Ecological information****12.1. Toxicity**

No information available.

**12.2. Persistence and degradability**

No information available.

**12.3. Bioaccumulative potential**

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**Aluminium Paint****12.6. Other adverse effects****! General regulation**

Toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

**! SECTION 13: Disposal considerations****13.1. Waste treatment methods****Waste code No.**

08 01 11\*

**Name of waste**

waste paint and varnish containing organic solvents or other hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

**! General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	<b>ADR/RID</b>	<b>IMDG</b>	<b>IATA-DGR</b>
<b>14.1. UN number</b>	1263	1263	1263
<b>14.2. UN proper shipping name</b>	PAINT	PAINT	Paint
<b>14.3. Transport hazard class(es)</b>	3	3	3
<b>14.4. Packing group</b>	III	III	III
<b>14.5. Environmental hazards</b>	Yes	Yes	Yes

**14.6. Special precautions for user**

No information available.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**Land and inland navigation transport ADR/RID**

Hazard label(s) 3

tunnel restriction code D/E

Special provisions 640E

Classification code F1

transport in "limited quantities" according to 3.4 ADR is possible

**Marine transport IMDG**

MARINE POLLUTANT

Transport as limited quantities according to 3.4 IMDG Code is possible.



---

**Transport/further information**

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

---

**! SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**VOC standard**

VOC content 49,2 %

VOC value 492 g/L

**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

---

**! SECTION 16: Other information**

**! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

**Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H411	Toxic to aquatic life with long lasting effects.