



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

06.01.2016

revision

18.06.2015 (GB) Version 8.2

### Label Remover

## ! SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Name of product

Label Remover

Code-Nr. 152060

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Technical Liquids

### 1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Postbox 48045, DE-8460 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail : msds@weicon.de

Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0

E-mail (competent person):

msds@weicon.de

### 1.4. Emergency telephone number

GIZ Bonn (German, English) Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

Manufacturer

WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

### 1.4. Emergency telephone number

Emergency advice

-

Phone -

GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)

Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

## ! SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard  
categories

Hazard Statements

Classification procedure

Flam. Liq. 2

H225

Skin Irrit. 2

H315

STOT SE 3

H336

Asp. Tox. 1

H304

## Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aquatic Chronic 2	H411	
-------------------	------	--

### Hazard Statements

H225	Highly flammable liquid and vapour.
H242	Heating may cause a fire.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07



GHS08



GHS09

### Signal word

Danger

### Hazard Statements

H225	Highly flammable liquid and vapour.
H242	Heating may cause a fire.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

### Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220	Keep/Store away from clothing.
P233	Keep container tightly closed.
P234	Keep only in original container.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing.



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

06.01.2016

revision

18.06.2015 (GB) Version 8.2

## Label Remover

P370 + P378	In case of fire: Use foam for extinction.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P420	Store away from other materials.
P501	Dispose of contents/container to hazardous or special waste collection point.

### Hazardous ingredients for labeling

Naphtha (petroleum), hydrotreated light, pentane

### ! Special rules for supplemental label elements for certain mixtures

Contains (R)-(+)-Limonene . May produce an allergic reaction.

### 2.3. Other hazards

Product has an anesthetic effect.

### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## ! SECTION 3: Composition/ information on ingredients

### 3.1. Substances

not applicable

### 3.2. Mixtures

#### Description

Compound

#### Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
109-66-0	203-692-4	pentane	10 < 25	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 2, H411
5989-27-5	227-813-5	(R)-p-mentha-1,8-diene	<= 0,1	Flam. Liq. 3, H226 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410
64742-49-0	921-024-6	Naphtha (petroleum), hydrotreated light	50 < 75	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336
64-17-5	200-578-6	ethanol	3 < 10	Flam. Liq. 2, H225 / Eye Irrit. 2, H319

#### REACH

CAS No	Name	REACH registration number
5989-27-5	(R)-p-mentha-1,8-diene	01-2119529223-47
64742-49-0	Naphtha (petroleum), hydrotreated light	01-2119475514-35
64-17-5	ethanol	01-2119457610-43

### ! Labelling for contents according to regulation (EC) No 648/2004, annex VII

less than 5 % scents

30 % and more aliphatic hydrocarbons



---

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.

#### In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off with water.

Consult a doctor if skin irritation persists.

#### In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

#### In case of ingestion

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Call for a doctor immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

#### Physician's information / possible symptoms

Unconsciousness

Coughing

Respiratory complaints

Headache

Confusion

skin irritation

### 4.3. Indication of any immediate medical attention and special treatment needed

#### Treatment (Advice to doctor)

If swallowed or in the event of vomiting, risk of entering the lungs.

---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

water mist

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

#### Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Ensure adequate ventilation.  
Use personal protective clothing.  
Keep away sources of ignition.

### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.  
Do not discharge into the drains or bodies of water..  
Do not discharge into the drains/surface waters/groundwater.  
Do not discharge into the subsoil/soil.

### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).  
Ventilate area concerned  
After taking up the material dispose according to regulation.

### 6.4. Reference to other sections

Safe handling: see section 7  
Disposal: see section 13  
Personal protection equipment: see section 8

---

## ! SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### ! Advice on safe handling

Avoid formation of aerosols.  
Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.  
Open and handle container with care!

#### General protective measures

Avoid contact with eyes and skin  
Do not inhale gases/vapours/aerosols.

#### Hygiene measures

At work do not eat, drink, smoke or take drugs.  
Wash hands before breaks and after work.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking  
Vapours can form an explosive mixture with air.  
Take precautionary measures against static discharges.  
Avoid effect of heat.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep in closed original container.

#### Advice on storage compatibility

Do not store together with animal feedstuffs.  
Do not store together with food.

#### Further information on storage conditions

Keep container tightly closed and store at cool and aired place.  
Protect from heat and direct solar radiation.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
64-17-5	ethanol	8 hours	1920	1000	EH40/2005
67-56-1	methanol	8 hours	266	200	EH40/2005
		Short-term	333	250	

**Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
109-66-0	pentane	8 hours	3000	1000	

**Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls****Respiratory protection**

Filter A or environment-independent breathing apparatus

Breathing apparatus in the event of aerosol or mist formation.

**Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

**! Eye protection**

tightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Sufficient ventilation and exhaustion.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

liquid

**Colour**

colourless, clear

**Odour**

characteristic

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
pH value	not determined				



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

06.01.2016

revision

18.06.2015 (GB) Version 8.2

**Label Remover**

	Value	Temperature	at	Method	Remark
<b>boiling range</b>	36 °C				
<b>melting point</b>	not determined				
<b>Flash point</b>	-35 °C				
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not applicable				
<b>Flammability (gas)</b>	not applicable				
<b>Ignition temperature</b>	200 °C				
<b>Self ignition temperature</b>					The product is not self-igniting.
<b>Lower explosion limit</b>	0,8 Vol-%				
<b>Upper explosion limit</b>	15 Vol-%				
<b>Vapour pressure</b>	573 hPa	20 °C			
<b>Relative density</b>	0,71 g/cm3	20 °C			
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					No or low immiscibility
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity dynamic</b>	not determined				
<b>Viscosity kinematic</b>	not determined				
<b>Solvent content</b>	100 %				
<b>Oxidising properties</b>	No information available.				
<b>Explosive properties</b>	The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .				
<b>9.2. Other information</b>	No information available.				

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No information available.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known.

### 10.4. Conditions to avoid

Keep away from heat.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

### Thermal decomposition

Remark No decomposition if used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	> 5840 mg/kg	rat		Naphtha
<b>LD50 acute dermal</b>	> 2920 mg/kg	rabbit		Naphtha
<b>LC50 acute inhalation</b>	> 25 mg/l (4 h)	rat		Naphtha
<b>Skin irritation</b>	irritant			
<b>Eye irritation</b>	non-irritant			
<b>Skin sensitization</b>	non-sensitizing			

#### Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

Swallowing may cause vomiting and diarrhoea.

Frequent persistent contact with the skin may cause skin irritation.

Irritates mucous membranes.

Inhalation causes narcotic effect/intoxication.

#### Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.





## SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicological effects

	Value	Species	Method	Validation
<b>Fish</b>	LL/EL/IL50 11,4 mg/l (96 h)	Oncorhynchus mykiss		Naphtha
<b>Daphnia</b>	LL/EL/IL50 3 mg/l (48 h)	Daphnia magna		Naphtha
<b>Algae</b>	LL/EL/IL50 30 - 100 mg/l (72 h)	Pseudokirchneriella subcapitata		Naphtha

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

No information available.

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

#### General regulation

Toxic to aquatic life, fishes and plankton.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Recommendations for the product

Remove in accordance with local official regulations.

#### Recommendations for packaging

Dispose of according to the local waste regulations.

## SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
<b>14.1. UN number</b>	1993	1993	1993
<b>14.2. UN proper shipping name</b>	FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), Pentan Mixture)	FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), Pentane mixture)	Flammable liquid, n.o.s. (Naphtha (petroleum), Pentane mixture)
<b>14.3. Transport hazard class(es)</b>	3	3	3
<b>14.4. Packing group</b>	I	I	I



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

06.01.2016

revision

18.06.2015 (GB) Version 8.2

## Label Remover

	ADR/RID	IMDG	IATA-DGR
<b>14.5. Environmental hazards</b>	Yes	Yes	Yes

### 14.6. Special precautions for user

Caution: FLAMMABLE LIQUID

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

### Land and inland navigation transport ADR/RID

Hazard label(s) 3

tunnel restriction code D/E

Classification code F1

### Marine transport IMDG

MARINE POLLUTANT

### Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

## ! SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### ! VOC standard

VOC content	100 %
VOC value	709 g/L

### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## ! SECTION 16: Other information

### ! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

### Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Danish MAL-code: 5-3

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.1

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.