

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Name of product** WEICONLOCK AN 301-48  
Code-Nr. 301480

**1.2. Relevant identified uses of the substance or mixture and uses advised against  
Recommended intended purpose(s)**

1-Component Adhesives and Sealants, anaerobic curing

**1.3. Details of the supplier of the safety data sheet****Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Postbox 48045, DE-8460 Münster  
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone ++49(0)251 / 9322 - 0  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

GIZ Bonn (German, English) Tel: ++49(0)228-19 240  
TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178  
433 7434 (24h Emergency Contact)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number****Emergency advice**

-  
Phone -  
GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)  
Tel: ++49(0)228-19 240  
TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178  
433 7434 (24h Emergency Contact)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315	
Eye Dam. 1	H318	
Skin Sens. 1	H317	
STOT SE 3	H335	

**Hazard Statements**

H315 Causes skin irritation.

H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS05



GHS07

### Signal word

Danger

### Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

### Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

### ! Hazardous ingredients for labeling

acrylic acid, Methacrylic acid, monoester with propane-1,2-diol

### 2.3. Other hazards

#### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**! SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

**3.2. Mixtures****Description**

Anaerobic adhesive / sealant

**! Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
79-10-7	201-177-9	acrylic acid	3 < 5	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Acute Tox. 4, H312 / Acute Tox. 4, H302 / Skin Corr. 1A, H314 / Aquatic Acute 1, H400
80-15-9	201-254-7	alpha,alpha-dimethylbenzyl hydroperoxide	1 < 2,5	Org. Perox. E, H242 / Acute Tox. 3, H331 / Acute Tox. 4, H312 / Acute Tox. 4, H302 / STOT RE 2, H373 / Skin Corr. 1B, H314 / Aquatic Chronic 2, H411
27813-02-1	248-666-3	Methacrylic acid, monoester with propane-1,2-diol	25 < 99,9	Eye Irrit. 2, H319 / Skin Sens. 1, H317
98-82-8	202-704-5	isopropylbenzene	0,3 < 1	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / STOT SE 3, H335

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

**In case of inhalation**

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

**In case of skin contact**

In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

**In case of eye contact**

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

**In case of ingestion**

Do not induce vomiting.

Seek medical advice immediately.

Rinse out mouth and give plenty of water to drink.

**4.2. Most important symptoms and effects, both acute and delayed****Physician's information / possible dangers**

Causes serious eye damage.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Fire-extinguishing activities according to surrounding.

### 5.2. Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolyse products.

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

#### Additional information

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

## ! SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

Ventilate area concerned

After taking up the material dispose according to regulation.

### 6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

No special measures necessary if used correctly.

#### General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

**Hygiene measures**

At work do not eat, drink and smoke.

Keep separated from food and feed.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Pay attention to general rules of internal fire prevention.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep only in original container.

**Advice on storage compatibility**

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with metals.

**Further information on storage conditions**

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

Store in a dry place.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
98-82-8	Cumene	8 hours	125	25	EH40/2005
		Short-term	250	50	

**DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	4,2 mg/kg bw/day	DNEL long-term dermal (systemic)	

**PNEC**

CAS No	Substance name	Value	Code	Remark
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	10 mg/l	PNEC sewage treatment plant (STP)	
		6,28 mg/kg	PNEC sediment, marine water	
		0,904 mg/l	PNEC aquatic, freshwater	
		6,28 mg/kg	PNEC sediment, freshwater	
		0,904 mg/l	PNEC aquatic, marine water	
		0,727 mg/kg	PNEC soil, freshwater	

**Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls****! Respiratory protection**

If ventilation insufficient, wear respiratory protection.

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short term: filter apparatus, Filter A/P2

**Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

The protective gloves to be used must comply with the specifications of EC directive 89/686/EEC and the resultant standard EN374.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

**Eye protection**

tightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Sufficient ventilation and exhaustion.

**! SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

liquid

**Colour**

green

**Odour**

characteristic

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not determined				
<b>boiling point</b>	not determined				
<b>melting point</b>	not determined				
<b>Flash point</b>	> 100 °C				
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not applicable				
<b>Flammability (gas)</b>	not applicable				
<b>Ignition temperature</b>	not determined				
<b>Self ignition temperature</b>	not applicable				
<b>Lower explosion limit</b>	not determined				
<b>Upper explosion limit</b>	not determined				
<b>Vapour pressure</b>	not determined				



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 07.01.2016

revision 27.04.2015 (GB) Version 8.1

**WEICONLOCK AN 301-48**

	Value	Temperature	at	Method	Remark
<b>Relative density</b>	1,1 g/cm <sup>3</sup>	25 °C			
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					No or low immiscibility
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity dynamic</b>	450 - 650 mPa*s	25 °C		Brookf-Visk.RVT Sp.2	
<b>Viscosity kinematic</b>	not determined				
<b>Oxidising properties</b>	No information available.				
<b>Explosive properties</b>	not applicable				
<b>9.2. Other information</b>	No information available.				

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

Reactions with Metal-Salts.

**10.4. Conditions to avoid**

Keep away from heat.

**10.5. Incompatible materials****Substances to avoid**

Metal, Metal-Salts

**10.6. Hazardous decomposition products**

Gases/vapours, toxic

Carbon monoxide and carbon dioxide.

Nitrous oxides (NO<sub>x</sub>)**Thermal decomposition**

Remark No decomposition if used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	382 mg/kg	rat		CAS: 80-15-9
<b>LD50 acute dermal</b>	500 mg/kg	rat		CAS: 80-15-9
<b>LC50 acute inhalation</b>	24,7 mg/l (4 h)	mouse		CAS: 98-82-8
<b>Skin irritation</b>	irritant			
<b>Eye irritation</b>	irritant - risk of strong eye injuries			
<b>Skin sensitization</b>	sensitizing			

#### Experiences made from practice

Sensitization through skin contact possible.  
 Risk of strong eye injuries.  
 Irritates mucous membranes.  
 Irritates eyes and skin.

#### Additional information

The product is to be handled with the caution usual with chemicals.  
 Other hazardous properties may not be excluded.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicological effects

	Value	Species	Method	Validation
<b>Algae</b>	EC50 2,6 mg/l (72 h)	Green algae		CAS: 98-82-8

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

No information available.

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

#### General regulation

Even in the event of low quantities penetration into the underground drinking water is contaminated.  
 Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.



## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste code No.**

08 04 09\*

**Name of waste**

waste adhesives and sealants containing organic solvents or other hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

**General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

## SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	-	-	-
14.6. Special precautions for user	No information available.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	not applicable		
Transport/further information	No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.		

## ! SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC standard**

VOC content 0 %

### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



## SECTION 16: Other information

### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

### Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.0

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.