

## Technical Datasheet

Create Date: 12.01.2016 - Page 1/1

# Mould Release Agent Wax P 500

## Health and Safety

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.



### solvent-containing

Wax P 500 as a release agent on a waxy basis for epoxy resins and polyurethanes. It is especially suitable for release processes from rough and/or porous surfaces.

## **Technical data**

| Basis                   | liquid, solventcontaining |
|-------------------------|---------------------------|
| Colour                  | white                     |
| Consistency             | pasty                     |
| Density at +20°C        | 80 g/cm <sup>3</sup>      |
| Consumption             | 50 - 150 ml/m²            |
| Application temperature | + 15 bis + 25 °C          |
| Operational temperature | bis 50 °C                 |

#### Pretreatment of the surface

The surface to be treated must be clean, dry and free of grease (e.g. cleaning and degreasing with WEICON Surface Cleaner).

#### Processing

Apply Mould Release Agent Wax with a fibre-free pulp cloth or with a lint-free paper cloth and polish uniformly. Repeat the process in case of new moulds or highly absorbing surfaces.

Excessive Mould Release Agent or residues can be removed with WEICON Surface Cleaner without leaving residual layers.

#### Storage

Unopened containers can be stored for at least 12 months after delivery at temperatures from +18  $^\circ$ C to +25  $^\circ$ C.

#### Note

Any product specifications and recommendations given herein must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do warrant the continuously high quality of our products being free from defects in accordance with and subject to our General Sales Conditions. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

## WEICON GmbH & Co. KG (Headquarter)

## WEICON Middle East L.L.C.

Königsberger Str. 255 · DE-48157 Münster P.O. Box 84 60 · DE-48045 Münster Germany

 Tel.
 +49 (0) 251 / 93 22-0

 Fax
 +49 (0) 251 / 93 22-244

 Fax
 +49 (0) 251 / 93 22-233 Export

 www.weicon.de · info@weicon.de

Jebel Ali Ind Area 3 · P.O. Box 118 216 Dubai · U.A.E

Phone +971 4 880 25 05 Fax +971 4 880 25 09 Mobile +971 50 545 99 83 www.weicon.ae · info@weicon.ae

#### WEICON Inc.

20 Steckle Place · Unit 20 Kitchener · Ontario · N2E 2C3 Canada

Phone +1 519 896 5252 Fax +1 519 896 5254 Cell +1 519 590 5168 www.weicon.ca · info@weicon.ca

# WEICON Kimya Sanayi Tic. Ltd. Şti.

Yenibosna Mahallesi Yalçın Koreş Caddesi Arifağa Sokak No: 29 Kat: 3 34530 Yenibosna – Istanbul Turkey www.weicon.biz.tr · info@weicon.biz.tr

#### WEICON Romania SRL

Str. Podului Nr.1 547176 Budiu Mic (Targu Mures) www.weicon.com · office@weicon.com