



However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

Health and Safety

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

excellent creeping properties

Top-Lub is a synthetic, transparent adhesive lubricant for the permanent lubrication of all types of highly stressed mechanical parts.

WEICON Top-Lub has a high adhesive and spinning strength and outstanding creeping properties. It is pressure-resistant, water-rejecting and can also be used during on-going operation in compliance with the respective safety regulations. It does not attack

The following plastics and elastomers are not attacked: PTFE, PE, PA, fluorine, butadiene and silicone rubber, polychloroprene. Of limited resistance are: PE-LD, POM, PP, and NBR.

WEICON Top-Lub can be used to force-transmitting bolts, gears and worm gears, high-speed machinery parts, joints and couplings, wheels and bearings and spring assemblies in many industrial sectors.

Technical data

| | |
|------------------------|-------------------------------------|
| Colour | colourless |
| Odour | mineral oil |
| Temperature resistance | -40 bis +200 °C |
| Shelf life (minimum) | 24 months |
| Special features | pressure resistant, water-repellent |

Processing

Surfaces to be treated must be clean and dry. Shake can and spray at about 15 cm from surface. Product may, thereafter, be applied also while parts to be lubricated are in operation, subject to respect of the relevant safety regulations.

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50 °C.

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation.

We do guarantee the continuously high quality of our products.

WEICON GmbH & Co. KG (Headquarter)

Königsberger Str. 255 · DE-48157 Münster
P.O. Box 84 60 · DE-48045 Münster
Germany

Tel. +49 (0) 251 / 93 22-0
Fax +49 (0) 251 / 93 22-244
Fax +49 (0) 251 / 93 22-233 Export
www.weicon.de · info@weicon.de

WEICON Middle East L.L.C.

Jebel Ali Ind Area 3 · P.O. Box 118 216
Dubai · U.A.E

Phone +971 4 880 25 05
Fax +971 4 880 25 09
Mobile +971 50 545 99 83
www.weicon.ae · info@weicon.ae

WEICON Inc.

20 Steckle Place · Unit 20
Kitchener · Ontario · N2E 2C3
Canada

Phone +1 519 896 5252
Fax +1 519 896 5254
Cell +1 519 590 5168
www.weicon.ca · info@weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.

Yenibosna Mahallesi Yalçın Koreş Caddesi
Arifağa Sokak No: 29 Kat: 3
34530 Yenibosna – İstanbul Turkey
www.weicon.biz.tr · info@weicon.biz.tr

WEICON Romania SRL

Str. Podului Nr.1
547176 Budiu Mic (Targu Mures)
www.weicon.com · office@weicon.com