

WEICON for the Rubber and Plastic Industry

WEICON RK 7000

High strength, fast curing construction adhesive with high tensile, shear and peel strength. Excellent adhesion on plastics (e.g. PVC, ABS, PMMA, fibre glass, phenol)

- polyurethane • epoxies and many other materials. High viscosity, therefore also suitable for vertical surfaces.



WEICON Easy-Mix Mixing and Dosing System

Cold-curing, solvent-free two-component systems with extremely strong bonding properties. Thanks to the modern mixing and dosing system, all three types can be cleanly and accurately automatically dosed, mixed and applied in only one working operation.

Type S 50 For quick repair and maintenance jobs. Ideal too for series production with short cycle times. Viscid, self-levelling, very short pot life (4-5 minutes)

Type N 50 Ideal for manufacturing processes with assembly and positioning carried out at different times. Viscid, self-levelling, normal pot life (45 minutes)

Type N 5000 Particularly suitable for connections where appearances are important. Liquid, self-levelling, shorter pot life (20 minutes)



WEICON Easy-Mix PE-PP 45

Fast-curing solvent-free 2-component acrylate adhesive with extremely strong bonding properties.

Especially suitable for structural bondings of low energy plastics such as PE, PP and many other materials, without pre-treatment of the surface. Pot life: approx. 2-3 min. Temperature resistant from -55°C (-67°F) to +80°C (+176°F).





WEICON Contact Cyanoacrylate Adhesives

Type VA 8312

- low viscosity, 20-40 mPa·s • very fast-curing
- for bonding of numerous rubber materials (e.g. solid rubber or cellular rubber) and plastics
- also suitable for bonding polyolefines (PE-Polyethylene, PP-Polypropylene) in combination with WEICON CA-Primer

Type VA 8406

- low viscosity, 20-50 mPa·s • very fast-curing
- for bonding of numerous rubber materials (e.g. solid rubber or cellular rubber) and plastics • especially suitable for bonding of EPDM elastomers, in cases where quick fastening is necessary • also suitable for bonding polyolefines (PE-polyethylene, PP polypropylene), PTFE and silicones in combination with WEICON CA-Primer

Type VA 250 Black

- high viscosity, 2000-3000 mPa·s
- slow-curing • residual elasticity after curing, therefore particularly suitable in ever changing climates
- not sensitive to longer term humidity
- temperature resistant from -50°C (-58°F) to $+135^{\circ}\text{C}$ ($+275^{\circ}\text{F}$) • black, rubber-filled adhesive
- excellent peel and shock resistance

Type VA 1460

- medium viscosity, 120-200 mPa·s
- longer curing • low odour and “blooming”
- for bonding numerous materials
- less sensitive to humidity when cured



WEICON Contact Primer for Polyolefines

Plastics that have been pre-treated with WEICON Contact Primer change their surface structure. Thereby, the joining of materials like polyethylene (PE) and polypropylene (PP), belonging to the polyolefine group, is made possible.

WEICON for the Rubber and Plastic Industry

WEICON Plastic Cleaner

The ideal product for cleaning and degreasing sensitive surfaces, e.g. window frames and roller blinds, plastic and rubber profiles. Recommended for the pre-treatment of surfaces for bonding.



WEICON Mould Release Agent

Prevents the adhesion (e.g. of WEICON Plastic Metal) to plastics, moulds, metals and tools due to its high sliding effect. Silicone-free.



WEICON Silicone Spray

A sliding and release agent for efficient production and maintenance. At the same time, it assumes the function of a preservative and care product for plastic, rubber and metal. Provides a durable separating film and good surface properties.



WEICON PTFE-Spray

Grease-free, clean, dry lubricant with excellent sliding properties. Due to the high PTFE percentage, the coefficient of friction is considerably reduced. Temperature resistant from -180°C (-292°F) to $+250^{\circ}\text{C}$ ($+482^{\circ}\text{F}$).





WEICON for the Rubber and Plastic Industry



WEICON Urethane

Liquide Polyurethane. Temperature resistant from -60°C (-76°F) to +90°C (+194°F). Flexible Casting and Coating Resin providing high impact strength and abrasion resistance.

For making: vibration dampers, assembling jigs
• flexible seals • rubber-like prototypes. Types with different shore hardness (D 45, D 60, D 80) are available.

WEICON Repair Stick Plastic



Easy to use: Cut off - knead - use
Especially for durable repairs of plastic parts* and fibre reinforced materials (GFRP, CFRP, fibre glass) with residual elasticity as well as for bondings of metal parts.

* except for plastics such as PE, PP, PTFE, etc.

WEICON Flex 310 M[®] Classic

A strong, sandable and overpaintable adhesive/sealant (POP hybrid polymer) that cures practically without shrinkage. Almost all materials, such as metals, wood, plastics, glass, ceramic, etc., can be bonded to themselves and among each other without the necessity to use a primer.

WEICON GmbH & Co. KG

Königsberger Str. 255 • DE-48157 Münster
Postfach 84 60 • DE-48045 Münster

Tel. +49 (0) 251 / 93 22-0
Fax +49 (0) 251 / 93 22-244
Fax +49 (0) 251 / 93 22-233 *Export*
www.weicon.de • info@weicon.de

WEICON Middle East L.L.C.

Jebel Ali Ind Area 3
P.O. Box 118 216
Dubai • U.A.E
Phone +971 4 880 25 05
Fax +971 4 880 25 09
www.weicon.ae
info@weicon.ae

WEICON Inc.

20 Steckle Place
Unit 20 • Kitchener
Ontario N2E 2C3
Canada
Phone +1 519 896 5252
Fax +1 519 896 5254
Mobile +1 519 590 5168
www.weicon.ca
info@weicon.ca

Distributed by:



Detailed information on these products is available from our single brochures and at www.weicon.de

The specifications and recommendations given in this brochure must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.